

PRECISION

**LIGHT WEIGHT
AND MANEUVERABLE**

When you need to be especially light on the turf, the Wright **Velke HC & LC** are ideal with large tires, excellent balance, and smooth controls. With a pump-motor drive, each model is ideally balanced to handle slopes and climb curbs. The larger LC versions are equipped with larger tires, reinforced frames, and a wider stance for great maneuverability and a low impact presence on commercial properties. The HC versions are ideally proportioned for grooming medium sized properties or getting in tight spaces, especially with a 32" mower.

- With deck sizes of 36", 48", 52" and 61" floating and 32" fixed deck options
- Intuitive controls
- Controls isolate vibration and are easy to squeeze
- Integrated Velke Sulky latch
- Large tires, perfectly balanced with high clearance to easily climb curbs
- Canister air cleaners for low maintenance and long life
- Flat-free caster tires



AVAILABLE NOW AT A WRIGHT DEALER NEAR YOU

For more information, call 301.360.9810 or visit wrightmfg.com



Height Select Pins



Hands-on Controls



Sulky side, back up and down latched

		HC			LC	
		32"	36"	48"	52"	61"
MOWER	Cutting Height Range	1.5 – 4.25"	1.5 – 4.25"	1.5 – 4.25"	1.5 – 4.25"	1.5 – 4.25"
	Deck Lift System	Shims, fixed deck	Shims, floating deck	Shims, floating deck	Shims, floating deck	Shims, floating deck
	Deck Construction	7 Gauge - AERO CORE™	7 Gauge - AERO CORE™	7 Gauge - AERO CORE™	7 Gauge - AERO CORE™	7 Gauge - AERO CORE™
	Blades (¼" thick, high-lift wings)	(2) 16.5"	(2) 18"	(3) 16.5"	(3) 18"	(3) 21"
	Spindles	Ductile Iron with durable seals	Ductile Iron with durable seals	Ductile Iron with durable seals	Ductile Iron with durable seals	Ductile Iron with durable seals
ENGINE	Makes Available	Kohler® Confidant Electric options				
	Hour Meter	Digital, Service Alert™	Digital, Service Alert™	Digital, Service Alert™	Digital, Service Alert™	Digital, Service Alert™
	Operator Controls	Upwards facing controls	Upwards facing controls	Upwards facing controls	Upwards facing controls	Upwards facing controls
	Hydro Pumps	Hydro-Gear® 10 cc	Hydro-Gear® 10 cc	Hydro-Gear® 10 cc	Hydro-Gear® 10 cc	Hydro-Gear® 10 cc
	Wheel Motors	Hydro-Gear® 12 cu in.	Hydro-Gear® 12 cu in.	Hydro-Gear® 12 cu in.	Hydro-Gear® 12 cu in.	Hydro-Gear® 12 cu in.
	Fuel Capacity	5.5 gal.	5.5 gal.	5.5 gal.	5.5 gal.	5.5 gal.
TRACTOR	Drive Tires	16 × 6.5 - 8 (4 ply)	16 × 7.5 - 8 (4 ply)	16 × 7.5 - 8 (4 ply)	18 × 8.5 - 8 (4 ply)	18 × 8.5 - 8 (4 ply)
	Caster Tires	9 × 3.5 - 4 flat free	9 × 3.5 - 4 flat free	9 × 3.5 - 4 flat free	11 × 4 - 5 flat free	11 × 4 - 5 flat free
	Speed Forward (mph)	5.5	5.5	5.5	5.5	5.5
	Speed Reverse (mph)	2.5	2.5	2.5	2.5	2.5
DIMENSIONS	Overall Length	72"	74"	69"	81.5"	83.75"
	Overall Width Deflector Up (Down)	33.5" (45.5")	36.5" (48.5")	49" (61")	53" (65")	62" (74")
	Dry Weight (lbs)	560	585	640	705	760

Many models are offered with rear discharge deck options. For current configurations and engine options see our online price sheet.
Warranty 2-Year Limited Warranty: Covers parts and labor. For further details, see your local Wright dealer.

AVAILABLE NOW AT A WRIGHT DEALER NEAR YOU

For more information, call 301.360.9810 or find our dealer locator at wrightmfg.com/dealer-locator