



Commercial Mower Owner's Manual

For Stander ZK serial # 43181 and higher until superseded



WARNING: READ THIS MANUAL BEFORE USING

Revised 08/2008

For your safety and for proper operation and maintenance read carefully and keep readily available for future reference.

Additional replacement owner's manuals as well as illustrated parts lists are available from your authorized Wright Dealer for a nominal charge. Also check www.wrightmfg.com for the most up to date product literature. Please note the complete model number and serial number of your Wright product.

For reference please note the following information at the time of purchase:

SERIAL # _____

MODEL # _____

DATE OF PURCHASE _____

Foreword

Welcome to the progressive group of mowing professionals who use Wright mowers. We are focused on giving you advanced engineering and quality construction in each mower we build.

This manual explains the features and promotes safer use of the mower. Please read it in its entirety and follow the instructions carefully so that you can have many years of safe and productive operation with your Wright product.

For service, remember that your Wright dealer knows your mower best and is interested in your satisfaction. Your dealer can provide you with quality maintenance and other assistance that you may need.

Please provide this manual to anyone who may operate the mower for them to study before operation. Additionally, make the manual and service documents available to anyone to whom you may sell the mower in the future. It is important that the next owner receive this information also.

As Wright Manufacturing, Inc. is constantly seeking ways to improve its products, the mower you have may differ slightly from the information and specifications in this manual. Wright reserves the option to make changes at any time without notice, in the process of continually improving our products.

Wright Manufacturing, Inc.



SAFETY ALERT

This is the safety alert symbol. It is used throughout this manual and on the mower's safety labels to alert you to potential personal injury hazards. Obey all safety messages that follow this symbol to avoid possible injury or death. Read these instructions carefully. It is essential that you read the instructions and safety precautions before you attempt to work on or use this unit.



WARNING

This symbol with the "WARNING" indicates a potentially hazardous situation which, if not avoided, could result in death or serious injury.



CAUTION

This symbol with the word "CAUTION" indicates a potentially hazardous situation which, if not avoided, may result in minor or moderate injury.

©1998-2008 Wright Manufacturing, Inc. All rights reserved. This material may not be reproduced or copied, in whole or part, without written permission from Wright Manufacturing, Inc. Grass Gobbler, Gobbler, Leaf Gobbler, Velke, Pro 1, X2, Stander, and Sentar are trademarks of Wright Manufacturing, Inc

TABLE OF CONTENTS

PRE-DELIVERY SERVICE OF MOWER BY DEALER	4
SAFETY INSTRUCTIONS	6
INTRODUCTION	6
GENERAL SAFETY INSTRUCTIONS	6
OWNER/USER NOTICE	6
USER QUALIFICATIONS.....	6
USER CLOTHING.....	7
INSPECT MOWER BEFORE EACH USE.....	7
REGULAR MOWER SAFETY MAINTENANCE	7
WORK AREA CONDITIONS & INSPECTION	7
INITIAL OPERATING SAFETY GUIDELINES	8
OPERATION IN FORWARD DIRECTION	8
OPERATION IN REVERSE	8
ZERO-RADIUS TURN OPERATION	8
OPERATION ON SLOPES	9
FUEL SAFETY	9
HYDRAULIC SAFETY.....	9
REPLACEMENT PARTS.....	10
OPERATING INSTRUCTIONS	11
MOWER INSPECTION.....	11
Basic Operation.....	11
HOW TO START THE MOWER	11
Before starting the engine.....	11
Starting the engine.....	11
HOW TO DRIVE THE MOWER.....	11
HOW TO STOP AND PARK THE MOWER	11
DRIVING THE MOWER OVER A CURB.....	12
MOWING ON VARYING TERRAIN	12
HOW TO ADJUST NEUTRAL.....	12
SPEED/SENSITIVITY ADJUSTMENT.....	12
HOW TO PERFORM THE TRACKING ADJUSTMENT.....	12
HOW TO TEST/USE THE BLADE CLUTCH/BRAKE SWITCH.....	13
HOW TO TEST THE OPERATOR PRESENCE CONTROL (OPC) SWITCH	13
SERVICE AND ADJUSTMENTS	14
Tire Maintenance and Pressure.....	14
Height-of-Cut	14
Deck Pitch.....	14
Belt Tension	14
Deck Lift Spring.....	14
Spring Platform.....	14
Oil Cooler Debris Screen Cleaning.....	14
Oil Cooler Cleaning.....	14
How to Move the Mower if the Engine Won't Start.....	14
Bleeding Air from the Hydraulic System	15
Battery Service	15
Cleaning the Mower.....	15
MAINTENANCE INTERVAL CHART	17
MAINTENANCE RECORD	18

Pre-Delivery Service of Mower by Dealer



If you are not completely familiar with the Safety Instruction Manual read it now before proceeding with the Pre-Delivery Service of the mower. Only your authorized Wright dealer should perform the Pre-Delivery Service of the mower.

The Wright Stander ZK is shipped completely assembled and has been adjusted and tested at the factory. However, due to jostling during the shipping process and the delivery time lapse the following items need to be repeated again before starting the mower. After you have uncrated the mower, follow these procedures in the order indicated:

- Remove spark plug wire from spark plug(s).
- Inspect the mower for any damage, unusual conditions or missing parts.
- Inspect the mower for all of its decals, especially the warning decals. There should be one blade warning decal on each side of the deck, the “shield missing” under the blade belt covers, and the dash decal.
- Check (and fill if necessary) engine oil level according to the engine manufacturer’s recommendation.
- Check (and fill if necessary) hydraulic fluid level. The level should be about 2” – 2 ½” below the top of the oil fill or using a dipstick, the level will be 4.25” from the bottom of tank. Use synthetic oil: Mobil1 15W-50.
- Check rear tire pressure - 18 to 22 psi. is recommended. It should be even on both sides. Use the higher pressures for heavier operators. Front Casters are equipped with non-pneumatic tires and do not require any air.
- Check the battery to see that the cables are tight and connected properly. The battery is 12 volts and is a maintenance-free battery. Only charge the battery if it will not start the mower properly.
- Remove the blade belt covers and inspect the belt and idler arm for smooth operation.
- Rotate the blade pulleys slightly to see if they rotate freely and all turn together. There will be resistance due to the clutch brake.
- Replace the blade belt covers.
- Check the cutter deck for proper adjustment. The deck should be approximately ¼” lower in the front than in the rear and the deck should be level side-to-side. If the deck is not adjusted properly, please adjust at this time. See Deck adjustments section of this manual for further instructions.
- Lubricate all moving parts (see Maintenance Items section of this manual).
- Fill fuel tanks with regular unleaded gasoline. Turn fuel valve, located on the right side of upright to the “ON” position. The down position controls the right tank, the up position controls the left tank. Center position is “OFF” and it is recommended to turn “OFF” when not operating.
- **DO NOT START THE ENGINE AT THIS TIME. FOLLOW THE NEXT PROCEDURE BEFORE STARTING.** The hydraulic system **MUST** be checked for proper operation before allowing wheels to operate on the ground.
- Set the rear of the machine on jack stands or blocks to raise rear wheels off the ground two or three inches and check to be sure that the mower will not fall off the supports you devise. (Do not support the mower’s weight on any part of the foot platform.) You must be able to stand on the mower. The stand(s) must be able to secure the mower from rolling off or away during the next procedures. Check under the mower deck for any debris or unusual conditions.
- With hand controls in the middle or neutral position, apply the parking brake.
- Open the manual bypass valves on side of each pump a half-a-turn counterclockwise.
- Reattach spark plug wires to spark plugs.
- Before starting the engine be ready to stop it if the wheels begin to turn with the brake on. (If this happens, check that the manual bypass valves on side of each pump are open at least a half-a-turn counterclockwise.)

- Start the engine according to the engine manufacturer's recommendation. Let the engine run at low RPM for several minutes to get the hydraulic fluid circulating through the pumps. While standing on the foot platform, release the parking brake. Now gradually close the manual bypass valves on top of each pump one at a time and see if the wheels start to move. If the wheels move when the hand controls are in neutral position, adjust the pump neutral adjustment allen screw. The manual bypass valves on side of each pump should now be firmly closed. (Do not tighten these bypass valves with a wrench. Only hand tighten). Now try moving the hand control levers, one at a time, forward and backward. Check to see if the wheels move forward and backward according to position of the levers. If not, service the hand control system. If the wheels stop when the hand controls are in the neutral position, the parking brake should now be applied.
 - Before testing the blade clutch/brake operation, make sure the area is clear and there is nothing vulnerable to being thrown from under the mower. No one should be near the mower deck or in its line of discharge at this time or at any time. The discharge chute deflector should be in the down position. The parking brake should now be applied. Move the engine throttle to $\frac{3}{4}$ speed setting.
 - Place your feet firmly on the foot platform and turn on the blade clutch switch. Run blades for a minute or so. Try engaging and disengaging the blades a few times about 10 seconds apart. If the blades do not start and stop in a short amount of time, service the clutch. With the blades on, now try lifting your feet off the foot platform to test the Operator Presence Control switch (OPC). The engine should die and the blades should stop in several seconds. If not, service the OPC system. Try this a couple of times.
 - Disengage the blades, set the parking brake, shut off the engine and remove the mower from the stand(s).
 - Drive the mower around on a level parking lot. **ZK's are being set at the factory in the slower setting of the Speed/Sensitivity Adjustment be used.** (See further in this manual for information on Speed/Sensitivity Adjustment.) Be sure that the mower drives in a straight line when both hand controls are held to the full speed position which is up against the stationary control bar. If not, see further in this manual for information on tracking adjustment.
 - As you drive the mower, listen for any unusual noises and test for irregular operation and adjust or service as necessary. Next, go over the safety information and operating procedures in this manual with the customer. **Instruct the customer in proper operation and observe the customer during their initial operation on a level parking lot. Make sure the customer is familiar and comfortable with the basic operation and use of the mower.**
 - **Dealer:** Please fill out and follow the instructions on the Product Registration Form and have the customer fill out his part of the form. After the Product Registration Form is filled out and signed by the customer and a representative from your dealership, please send or fax it within 14 days to your Wright Manufacturing Distributor according to the directions on the Form. Then give the customer his copy of the registration form and then keep your copy and mail the remaining copies of the form to your Wright Manufacturing Distributor. **The limited warranty is not valid unless the mower is registered and all of the above steps are taken.** Remember, the purchaser is both your and our customer and his satisfaction is very important. Thank you for supporting our products.
-
- The mower is now ready for delivery to your customer



WARNING

This symbol with the word "WARNING" indicates a potentially hazardous situation which, if not avoided, could result in death or serious injury.



CAUTION

This symbol with the word "CAUTION" indicates a potentially hazardous situation which, if not avoided, could result in minor or moderate injury.

SAFETY INSTRUCTION MANUAL

**TO WRIGHT MOWER USERS & OWNERS: READ THIS MANUAL BEFORE USING.
PLEASE BE CAREFUL!**

INTRODUCTION

This mower is built to the highest standards in the industry. However, carelessness or operator error may result in serious bodily injury or death. Accident and hazard prevention are dependent upon the awareness, concern, wisdom, and proper training of the personnel involved in the operation, transport, maintenance, and storage of the equipment. Make sure every operator is properly trained and thoroughly familiar with all of the information in this manual before operating the equipment.

GENERAL SAFETY INSTRUCTIONS

The Wright Stander ZK is designed with your safety in mind. It has the following safety systems with which you should be familiar:

- The warning decals on the mower including the instrument panel warning
- The blade switch must be "off" before starting the engine
- Your feet must be on the foot platform in order to engage the blades
- If you remove your feet from the foot platform while the blades are running the engine will stop and the blades will brake in seconds
- Letting go of the hand controls will stop the wheels instantly
- Spring loaded chute deflector helps reduce trajectory of thrown objects
- Belt/pulley covers on cutter deck
- Anti-tip rollers are provided at the rear of the mower to minimize the possibility of tipping back and over on the operator



WARNING

Owner/User Notice:

The owner's/user's obligation is to instruct themselves and all potential users in the safe operation of this equipment and be sure they read and follow the instructions in this safety manual and other material provided by Wright Manufacturing, Inc. before using or allowing others to operate the equipment. Do not operate this unit unless you carefully read, understand and follow the assembly, installation, and safety instructions contained in this manual and the warning decals provided on the unit. Do not allow other persons to use this unit unless you make sure they carefully read, understand and follow these instructions. Never allow children to operate or play on the unit.



WARNING

User Experience and Qualifications:

This product is designed for use by physically fit, experienced, professional commercial mower operators who have a **minimum of 160 hours** of experience operating twelve horsepower and greater industrial mowers. Operators must be 18 years or older and weigh at least 120 pounds and no more than 350 pounds. They must have read and understood this manual. **DO NOT** allow children to operate the mower. Do not allow adults to operate the mower without proper instruction mentioned above. Never allow passengers on the mower.



User Clothing:

DO NOT operate the mower while wearing sandals, tennis shoes, sneakers, or shorts. Always wear long non-baggy pants. Wear high-top leather work boots with thick, textured tread, soft-rubber soled at all times. Hard or smooth soled shoes are too slippery for a good footing on mower platform. NEVER wear loose-fitting clothing or jacket pockets that can get caught to the handlebars or control levers of any mower you drive. Wearing safety glasses, ear protection and safety shoes is advisable and required by some local ordinances and insurance regulations.



Inspection of Mower Before Each Use:

DO NOT use the mower if any parts are not maintained in good operating condition. Examine the moving parts prior to each use. Look for excessive wear, bald or worn tires, cracks in parts, loose or missing bolts, cotter, linchpin or "hair" pins or cable yoke pins and replace before operating the mower. Make sure all safety equipment provided with the mower is in good operating order, including all the warning decals and the required operator-presence device which stops the engine and blades when the foot-operated Operator Presence Control (OPC) switch is released. (To test the OPC, follow instructions in the Operating Instructions section of this manual.) Inspect the two anti-tip rollers and their respective bolts at the rear of the mower for tightness and proper operation. Be sure that all parts of the hand-operated transmission control system are tight and secure. This is to reduce the possibility that the mower could have a loss of control or safety.



Scheduled Mower Maintenance Safety:

Replace worn tire(s) with less than 3/32" of any tread groove left. Use tires with the tread pattern specified by Wright Mfg., Inc. only. DO NOT change the engine governor settings or over-rev the engine contrary to engine manufacturer specifications. Keep the Wright mower in good operating condition, and keep safety devices and shields in place and in working condition. Keep all nuts, bolts, and screws tight to be sure the

equipment is in safe working condition. Check the blade mounting bolts for proper tightness every eight (8) hours of operation. Check the blades for excessive wear and sharpness every four to eight (4-8) hours of operation. Replace excessively worn blades. Sharpen dull blades. The mower should not be used after the blades or other part of the mower strikes a foreign object, until conducting a thorough inspection and any damage is repaired. See the instructions in the Recommended Maintenance section of this manual for other items of required maintenance.



Work Area Conditions and Inspection:

Prior to operating the unit, carefully inspect all lawn/ground areas where you plan to use the mower for hidden, hard-to-see objects or uneven ground that may be hidden in the grass. Clear the work area of moveable objects such as wires, rocks, glass, etc. that might be picked up by the mower and dangerously thrown. Remove, if possible, or mark the location of all immovable objects or irregular areas and be sure not to hit them with any part of the mower, its deck or the blades. Obstacles such as holes, abrupt changes in ground contour, tree trunks, stumps or roots, pipes protruding from the ground, paving edges, etc. in the path of operation can abruptly turn or stop the mower. This could throw you off the mower or into and possibly over the handle bars causing serious injury or death. ***The faster you are moving, the more potential there is for injury.*** Mow only in daylight or in good artificial light. Keep away from drop-offs, the edges of ponds, streams, pools, etc. especially at the bottom of slopes. Do not mow when children or others are around. When the Wright mower is in use, never direct the grass discharge toward bystanders, traffic, cars or buildings nor allow anyone near the machine while in operation. Thrown objects can pass through glass windows and some walls of buildings. There is extreme risk of danger from thrown objects or being cut by the blades of the mower or being run over if you lose control. Never operate the mower in an enclosed area without good, approved ventilation. Exhaust fumes are dangerous.



Initial Operating Safety Guidelines:

- Read and understand the warnings on the instrument panel of the mower.
- Keep a firm hold on the stationary handle at all times.
- Keep both feet on the foot platform at all times.
- Know the controls and how to stop quickly.

- Before attempting to start the engine, follow all starting instructions below and in the engine operator's manual.
- Look behind before backing up.
- Before leaving the operator's position, even momentarily, turn off the blade clutch engagement switch and apply the parking brake. Keep others from coming near the mower. Get back on the mower as soon as possible.
- When leaving the Wright mower unattended, turn off the blade clutch engagement switch, apply the parking brake, stop the engine and remove the key. Never leave the machine unattended on a slope in case someone disengages the parking brake which would be hazardous if the mower were to roll.
- When transporting, driving onto transport vehicles, into buildings, across parking lots or otherwise not mowing grass, turn off the blade clutch engagement switch to reduce risk of thrown objects and rotating blade hazard. After coming to a stop apply the parking brake, stop the engine and remove the key.
- Before performing any maintenance or repair service, disengage power to blades, apply the parking brake, stop the engine, remove ignition key and spark plug wire from spark plug(s).
- All operators of this mower should exercise caution when driving this mower at high speeds. Sudden stops from excessive speeds may cause serious injury.
- DO NOT allow inexperienced people to operate the mower until they have read and understood these safety instructions. **Operate the mower at slower speeds while becoming familiar with it.**
- The grass discharge chute deflector must be installed at all times and in the down position except that it may be raised when the grass catcher is completely installed or a mulch kit is completely installed.
- If the mower discharge clogs, turn off the blade clutch switch, apply the parking brake, stop the engine and remove the key before removing obstruction.
- Keep all shields and covers in place, especially grass discharge chute deflector and the blade belt covers.
- Keep hands, feet and clothing away from rotating parts, especially the rear wheels, blades, engine flywheel, belts and pulleys.
- Do not touch engine or muffler while engine is running or soon after it is stopped. These areas can be so hot as to cause severe burns.
- **Clean grass, leaves and lubricant spills from surfaces after use to prevent fire hazard.**

- Be alert for traffic when crossing roads or operating near roadways.
- Before climbing curbs, crossing gravel drives, sidewalks or roads, turn off the blades, lift them into transport position, and wait for them to stop.



Operation In Forward Direction

Always keep a firm grip on the mower stationary handlebar with both hands. Operate the mower slowly until you become familiar with how the mower operates. Do not operate the mower faster than conditions allow. For example, hills, wet or bumpy ground, dim light or high grass are all conditions requiring slower speeds. Never operate the mower at the highest speed unless you are on level, wide, open areas of clearly visible ground or transporting on paved areas. Speeding with any mower is dangerous, and so is traveling faster than conditions should permit on this mower. Sudden stops from excessive speed or falling off the mower may cause serious injury or death.



Operation In Reverse

Always keep a firm grip on the mower stationary handlebar with both hands. Keep both feet firmly on the foot platform. Look behind you before backing to prevent injuring yourself or anyone behind you. Operate the mower very slowly, inching it backward until you become familiar with how the mower operates. Always operate slowly if in an awkward location or position. While backing up, never place your foot or feet on the ground near the back edge of the mower to prevent serious personal injury if the mower were to run over you.



Zero-Radius Turn Operation

During zero-radius turns (when one mower wheel rotates backwards while the other rotates forward) drive extra slowly to reduce the possibility of losing traction, or control, or becoming dizzy. This will help prevent you from being thrown off the mower. Be aware that if you do a turn on a slope you may go through all of the orientations to a slope mentioned below and must handle the mower accordingly.



Operation on Slopes

DO NOT operate on steep slopes. Do not operate the mower on slopes steeper than you can feel secure about the traction of the tires and the stability of the mower. Do not operate the mower on slopes at all when the grass is wet. There is a danger of suddenly sliding sideways or down the hill. When operating on a slope, travel across the grade whenever possible, not in an up or down pattern. Reduce speed and exercise extreme caution on slopes and in sharp turns to prevent tipping or loss of control. Be especially cautious when changing direction on slopes.

When pointing up a slope, your mower has the most weight on the drive wheels and therefore the most traction at the tires. However, this is the angle that it has the most tendency to tip back (“pop a wheelie.”) This is the preferred angle for mowing small areas of steeper slopes.

Recommendations for this angle:

- Lean as far forward as possible to add your weight to the front of the mower.
- Accelerate gently. Do not accelerate quickly to avoid “popping a wheelie”.
- If backing down the hill, do not stop suddenly but slow down gradually.

When pointing down a slope, your mower has the least weight on the rear drive wheels and therefore the least traction at the tires. This is the angle that the mower has the most tendency to slide. However, this is the angle that it has the least tendency to tip back. Avoid this angle, as it has the least advantage for your mower.

Recommendations for this angle:

- Lean back with arms stretched out straight while holding onto the stationary handlebar. This transfers more of your body weight to the rear drive wheels for more traction.
- Do not change speed suddenly to minimize the tendency of going into a slide. Accelerate and decelerate gently. If you ever go into an uncontrolled slide while pointing down a slope the recommended procedure is to let go of the handles and jump off if necessary. Otherwise, control the mower gently and stay off slopes that tend to make the wheels slide.

When crossing a slope sideways, your mower has the average amount of weight on the drive wheels versus the front wheels, similar to level ground. However, this angle leaves the least weight on the higher side drive wheel, tending to

make it slip. This is the preferred angle for mowing large areas of gentle slopes.

Recommendations for this angle:

- Lean back. This adds weight to the rear drive wheels and will allow you to mow more quickly across the slope without sliding. The mower function and comfort will vary depending on mowing environment, operator driving style and preference.
- To reduce the chances of “popping-a-wheelie”, do not accelerate quickly.

Note: Excessively worn tire tread is dangerous. Replace tire(s) with less than 3/32” of any tread groove left. Use tires with the tread pattern recommended by Wright Mfg., Inc. only. Keep the tire pressure in the drive tires between 18 and 22 psi. Higher pressures will cause the tires to have less traction which may prevent safe operation.



Fuel Safety

Handle gasoline with care – it is highly flammable. Do not smoke while handling gasoline. Use an approved gasoline container. Never remove the fuel cap or add gasoline to a running or hot engine or an engine that has not been allowed to cool for several minutes after running. Never fill the tank indoors and always clean up spilled gas. NEVER store the equipment with gasoline in the tank inside a building where fumes may reach an open flame or spark. Allow the engine to cool before storing in any enclosure.



Hydraulic Safety

Keep body and hands away from pin holes or fittings that eject hydraulic fluid under high pressure. Use paper or cardboard and not hands to search for leaks. Hydraulic fluid escaping under high pressure may have sufficient force to penetrate skin and cause serious injury. If foreign fluid is injected into the skin, it must be surgically removed within a few hours by a doctor familiar with this form of injury or gangrene may result. Seek medical attention immediately. Make sure all hydraulic fluid connections are tight and all hydraulic hoses and lines are in good condition before starting your Wright mower. Hydraulic fluid is under high pressure. If you need service on your hydraulic system, please see your authorized Wright dealer.



Replacement Parts

Use of parts other than specified parts supplied by Wright Manufacturing, Inc. may compromise the safe use of the mower, are not recommended and their use could void the warranty. Always check with your Dealer or the Wright Mfg website for the latest Illustrated Parts List for your equipment.

Wright is fully concerned with your safety. Please read the above again and again until you fully understand the methods to promote the safest operation possible.

**REMEMBER – YOUR MOWER CAN BE
ONLY AS SAFE AS THE OPERATOR.
FAILURE TO FOLLOW SAFE
OPERATING PRACTICES MAY RESULT
IN SERIOUS INJURY OR DEATH.**

OPERATING INSTRUCTIONS



If you are not completely familiar with the Safety Instruction Manual read it now before proceeding with the operation of the mower. REMEMBER THERE ARE CERTAIN PRECAUTIONS LISTED IN THIS MANUAL THAT YOU MUST NOW TAKE BEFORE STARTING THE MOWER.

Inspect Mower Before Each Use

Inspection of Mower: Do not use the mower if any parts are not maintained in good operating condition. Examine all moving parts prior to each use. Look for excessive wear, bald drive tires or worn out front tires (normally smooth), cracks in parts, loose or missing bolts, cotter, linchpin or “hair” pins or cable yoke pins and replace before operating the mower. Make sure all safety equipment provided with the mower is in good operating order, including all warning decals and the operator-presence device which stops the engine and blades when the foot-operated Operator Presence Control (OPC) switch is released. To test the OPC, follow the instructions given later in this manual. Inspect the two anti-tip rollers and their respective bolts at the rear of the mower for tightness and proper operation. Ensure that all parts of the Quad-Lever™ control system are tight and secure. This is to reduce the possibility that the mower could have a loss of control or safety.

Basic Operation: The following procedures are to guide you through the basic operation of the mower. ***You should be a qualified mower operator according to the safety section of this manual. If this is your first time, operation should only be done with the assistance of your dealer on a level area.*** You should go through each step, in the order indicated, every time you start the mower.

How to start the mower

Before starting the engine

- Make sure the control levers are in the exact neutral position
- Apply the parking brake if it is not already set.
- Turn OFF the blade engaging switch if it is on.
- Turn fuel valve to the “ON” position.

Starting the engine

Electric Start:

- Start the engine according to the engine manufacturer’s recommendation, see engine manual. Set the throttle control lever near mid throttle, pull out on the choke control knob and turn the key to the start position. Do not engage the starter for more than ten (10) seconds at a time. This may overheat the starter and the wiring systems. Wait ten (10) seconds between attempts. If the engine does not start after

several attempts or stalls frequently, take the mower in for service.

After starting the engine according to the engine manufacturer’s recommendation, push in on the choke control knob to open the choke valve, let the engine run for several minutes to get the hydraulic fluid circulating through the pumps, etc. and to allow the engine to warm up. Do not over-rev a cold engine.

Unusual noises or irregular operation:

As you drive the mower, listen for any unusual noises and test for irregular operation and adjust or service as necessary.

How to drive the mower

While standing, both feet should be firmly placed on the foot platform. Set the engine speed about a fourth of the way from idle. Release the parking brake. Now try moving the hand control levers, one at a time, very slightly, forward and backward. Check to see if the wheels move forward and backward according to the position of the levers. If not, check to see that the pump release valves are closed. With both feet still firmly placed on the foot platform, increase the engine speed to about half of the way from idle speed. Release the parking brake. The higher engine speed will make the controls much more responsive and the mower much quicker; **Use caution if it is your first time.** Now try moving the hand control levers, one at a time, very slightly, forward and backward. Gradually increase your speed until you are well acquainted with the operation of the hand controls and the mower’s behavior. After gaining a good feel for how the mower handles, gradually attempt higher engine speeds until familiar with operation at full throttle engine speed.

How to Stop and Park the Mower

Come to a complete stop. If the blades are on, turn them off using the switch on the instrument panel. *Make sure the control levers are in the exact neutral position.* Set the parking brake, reduce the engine speed to idle, shut off the ignition switch to stop the engine and then remove the key from the ignition switch. The mower is now parked. Do not leave mower unattended on a sloped surface.

How to Drive the Mower Over a Curb

To climb a curb, first see the [Safety Instruction Manual](#) section of this manual, especially the parts on:

- Initial Operating Safety Guidelines
- Operation In Reverse
- Operation In Forward Direction

Next, raise the mower deck into the locked transport position. This is the highest position for the mower deck. Then drive the mower in reverse at a 45 degree angle to the curb (with the left side of the mower closest to the curb) until you are within an inch or two of the left-rear tire hitting the curb. Stop and then gradually bump into the curb with that tire until it is just on top of the curb. If the tire slips even while lurching the mower into the curb, then the curb is too high and you should use ramps or find another way. The mower should still be at a 45 degree angle to the curb. Now, while maintaining the same angle to the curb, continue to back up until the right-rear tire is close to the curb. Using the same technique lurch the right tire onto the curb. After both wheels are on top of the curb, turn the mower counterclockwise and back up so the left caster wheel comes over and last should be the right caster wheel as the mower is twisting to the left (counterclockwise). The technique works the best if you try not to drive backwards at a near 90 degree angle to the curb but get all of the wheels to go over while the mower is moving at least a 45 degree angle to the curb. To drive off a curb, first try driving up onto it to make sure the curb is not too high. If the curb is not too high, drive the right-front caster off first while driving toward the curb at a 45 degree angle (the curb should be to your right). Then, maintain that 45 degree angle so the left caster goes over, then the right-rear wheel, then the left rear wheel.



Never drive straight onto or off a curb.

Never drive straight onto or off a curb. If you do the whole procedure at a very sharp angle it will tend to minimize the contact of the mower deck with the curb and you will be able to more safely control the mower.

How to Use the Mower on Varying Terrain

See the [Safety Instruction Manual](#) section of this manual, especially the parts on:


- Initial Operating Safety Guidelines
- Operation On Slopes
- Operation In Reverse
- Operation In Forward Direction
- Operation During Zero-Radius Turns

How to Adjust Neutral

Neutral refers to the mower movement when the engine is set to full throttle, parking brake is off, and the control levers are in the neutral position. The mower should not move forward or backward during this time. If the mower is moving forward or rearward, the neutral setting must be adjusted. The hydraulic pump has a Return-to-Neutral (RTN) device built into the linkage of the pump. To make the adjustment, loosen the 1/4" allen bolt and rotate the RTN device until the neutral position is found and then retighten the 1/4" allen bolt. Use care not to over tighten the allen bolt.

How to Change the Speed/Sensitivity Adjustment

The controls are initially set with the Speed/ Sensitivity adjustment in the slower, less sensitive position. This setting has the ground speed 10-15% slower than the mowers capability. With operators not completely familiar with the



mower operation the operator may desire to leave the controls in the slow hole setting until becoming familiar with the operation. The faster setting has a corresponding increase in the sensitivity of the controls. In other words, a given amount of movement of the control levers will cause about a 10-15% increase in the ground speed making the controls more sensitive. **After stopping the engine**, the adjustment is made by removing rod ends connected to the control rods from the current holes in the control levers and reinstalling them into the alternate holes. The holes closest to the operators position are for the faster, more sensitive setting and the holes farthest from the operators position are the slower, less sensitive setting. You must then perform the Tracking Adjustment described below.

How to Perform the Tracking Adjustment

First ensure that the tire pressure is equal on both rear drive tires. Drive the mower on a level parking lot with engine at full throttle. Check that the mower drives in a straight line when both hand controls are held to the full speed position which is up against the stationary control bar. If not, park the mower and **stop the engine**. Before proceeding to adjusting the mower tracking, check and make sure both controls move freely through the forward and reverse range. Make sure that debris has not hindered the movement of the upper and lower control rods and linkages. If all control linkages move freely and mower tracking is off, proceed to the next step.

Tracking in the Slow Hole Setting

It is essential to start with the lower (and shorter) control rods located near the pumps. With the control levers in the neutral position, the right and left lower control rod should be adjusted to allow their respective torsion bar to remain level at the end connected to the lower control rod. Specifically, with

the pump in the Return-To-Neutral position, the lower rod end should be the same height as the rigidly fixed ball joint connected on the same end of the torsion rod. **NOTE:** *This adjustment may not be necessary if tracking is slightly off. Upper control rods should be the only adjustment required.*

Perform this adjustment on both the right and left side. Now that the lower end of both torsion rods are set, proceed to the upper control rods connected to the control levers.

Loosen the jam nuts on both ends of the upper control rod. Note: the Speed Sensitivity setting should be set to the slow position. Rotate control rod to either lengthen or shorten. So, if the mower is tracking to the left, either the left side needs to go faster (by lengthening the upper control rod on the **right**) or the right side needs to go slower (by shortening the upper control rod on the **left**). If the mower is tracking to the right, either the right side needs to go faster (by lengthening the upper control rod on the **left**) or the left side needs to go slower (by shortening the upper control rod on the **right**).

Tracking in the Fast Hole Setting

It is essential to start with the lower (and shorter) control rods located near the pumps. With the control levers in the neutral position, the right and left lower control rod should be adjusted to allow their respective torsion bar to remain level at the end connected to the lower control rod. Specifically, with the pump in the Return-To-Neutral position, the lower rod end should be at the same height as the rigidly fixed ball joint connected on the same end of the torsion rod. Perform this adjustment on both the right and left side. Now that the lower end of both torsion rods are level, proceed to the upper control rods connected to the control levers.

Loosen the jam nuts on both ends of the upper control rod. Note: the Speed Sensitivity setting should be set to the fast position. Before changing the length of the control rods several facts are important to know.

In the *faster* Speed/Sensitivity setting neither control rod should be shortened so much that at full speed it pulls the pump control lever (on the sides of the pumps) against the pump's internal stop. The pumps have an internal stop that is not designed to take this type of force and could eventually cause pump leakage or other damage to the pump. Therefore, to reach the maximum capable speed, the rods should be lengthened one turn at a time until you can feel in the hand control that the internal stop has been contacted with the control handles in the maximum forward position. Then shorten the cable one turn. This will enable the stationary bar to stop the control handle and protect the internal pump stop from damage. Remember, this procedure **does not apply** if the Speed/Sensitivity Adjustment is in the slower setting.

So, if the mower is tracking to the left, either the left side needs to go faster (by lengthening the upper

control rod on the **right**) or the right side needs to go slower (by shortening the upper control rod on the **left**). If the mower is tracking to the right, either the right side needs to go faster (by lengthening the upper control rod on the **left**) or the left side needs to go slower (by shortening the upper control rod on the **right**).

The only reference point to limit the adjustment from becoming extremely off is the relative position of the pump internal stop and the stationary bar in the *faster* Speed/Sensitivity setting. Therefore, if everything is extremely off either because you are installing new parts or other reasons you should only use the *faster* Speed/ Sensitivity setting to get the tracking to be accurate. After getting the mower to track straight, readjust the neutral adjustment, if necessary. It is normal to need to make these adjustments from time to time as the linkage breaks in or wears.

Test/Use the Blade Clutch/Brake Switch

Before testing the blade clutch/brake operation, make sure the area is clear and there is nothing vulnerable to thrown objects from under the mower. No one should be near the mower deck or in its line of discharge. The discharge chute deflector should be in the down position. The parking brake should now be applied. Move the engine throttle to $\frac{3}{4}$ speed setting. (When mowing, the engine speed should always be at its highest setting. The engine governor will regulate the engine according to the different mowing conditions at that setting.) Place both feet firmly on the foot platform and turn on the blade clutch switch. Run blades for a minute or so. Try engaging and disengaging the blades a few times about 10 seconds apart. If the blades do not start and stop in a few seconds each time, inspect the clutch or contact your local Wright dealer. Under mowing load, the clutch's life will be the greatest at the highest RPM setting.

How to Test the Operator Presence Control (OPC) Switch

With the parking brakes applied and the blades ON, try lifting your feet off the foot platform to test the Operator Presence Control switch (OPC). The engine should kill and the blades should stop within a few seconds. If not, service the OPC system or contact your local Wright dealer.



Service and Adjustments

Tire Maintenance and Pressure

Excessively worn tire tread is dangerous on all hills. Replace drive tires with less than 3/32" of any tread groove left. Use tires with the tread pattern recommended by Wright Mfg., Inc. only. Keep the tire pressure in the drive tires between 18 and 24 psi. Higher pressures will cause the tires to have less traction which will force you to go slower and with less safety and give you a harder ride. Front Casters are equipped with non-pneumatic tires and do not require any air. They do not have any tread but should be replaced when excessively worn.

Height-of-Cut

Before adjusting the height-of-cut be sure the mower blades are not spinning, and all four tires have proper air pressure. Check for even tire wear. The height-of-cut can be adjusted the following ways:

- Pull the deck lift lever on the right hand side of the mower towards the rear of the mower until it clicks once into the locked transport position. Then set the mower blade height with the selector pin on the left hand side of the mower. Once the proper height setting is set on the left, pull back on the deck lift lever on the right hand side and then lower the lever towards the front of the machine until it stops at the set height of cut.

Deck Adjustments

The mower deck can be adjusted for pitch and side-to-side lever. Pitch is the relationship between the front of the deck and the rear of the deck in regards to height of cut. In most cases, a positive pitch (front of the deck lower than the rear of the deck) of 1/4" is the optimum setting. These two adjustments can easily be made by using the deck lift rod assemblies attached to the front deck arms and the threaded deck hangers located at the rear of the deck frame. These hangers are connected to the chains that hold the deck. Adjust the rear deck hangers (by using a socket through the hole above the toe area of the platform) to achieve a 1/4" pitch. These hangers are right-handed threads. If you raise any of these settings above the factory setting, the deck may not raise all the way up into transport position. Be sure and check the deck height of cut range after any adjustments are made to these hangers to ensure that the height of cut adjustments work properly. If unable to make the adjustments needed by only using these hangers, contact your dealer for assistance.

Belt Tension Adjustment

The pump drive belt is self-adjusting, and requires no adjustment, just replacement. The blade drive belts are self-adjusting also and require no adjustment, just replacement.

Deck Lift Spring Adjustment

To adjust deck spring tension, tighten or loosen the eye-bolt Nylock jam nut located in the front tank bracket. If tightening for more lift assist make sure not to over tighten creating the deck to hop over rough terrain.

Spring platform Adjustment

The factory setting is both springs set at the most forward position. The more rearward the spring position, the stiffer the platform gets. Adjustment will be to preference of feel. The two adjustment springs should at all times, be positioned next to each other not one forward or back more than the other. To adjust, loosen each spring retaining bolt from the top just enough to slide it, then tighten with impact wrench. The nut may spin using hand wrench. NOTE, do not loosen too much, if the nut falls off, the foot platform will have to be removed to reinstall. There is an extra hole for a third spring for operators heavy enough to bottom out the duel spring stock set up.

Oil Cooler Screen Removal and Cleaning

Your Stander ZK is equipped with an oil cooler, the oil cooler debris screen will need to be **cleaned several times a day**. Clean more often in bush hog conditions. To clean, "**STOP ENGINE**" lift thigh pad for access, either wipe screen or remove screen for cleaning. To remove screen, lift and rotate spring locks to free the screen. The screen is bowed to

prevent a rattle and should be installed hump down, like a “U”. Using compressed air or water to clean may or may not be necessary.

Oil Cooler Removal and Cleaning

Clean oil cooler weekly. Clean more often in dry conditions. To remove oil cooler for a thorough cleaning “**STOP ENGINE**”, lift thigh pad for access. Loosen knob as far as necessary to slide the cooler back about 3/8 – 1/2" and then lift up and out. (The cooler knob does not need to be removed) Watch cooler hoses so they do not snap pump fans. The debris screen should be removed before blowing cooler out from the bottom. When reinstalling the cooler, make sure the cooler hoses do not interfere with the fans and ensure the cooler housing is secure under the four tab points of the cooler bracket. Tighten knob securely.

How to Move the Mower if the Engine Won't Start

Rotate both of the manual “release” valve levers on the rear of each hydraulic pump about ½ turn counterclockwise. It is important not to over tighten these levers. Damage may occur to the pump if this valve is over tightened.

Bleeding Air from the Hydraulic System

Whenever **servicing the hydraulic system, it is of the utmost importance to keep any dirt or debris from getting into the system.** When any of the hydraulic parts are disconnected or removed or when the oil is changed, air must be bled from the system. If air is entrained in the system, loss of power, excessive heat, and damage to the hydraulic pumps may occur. First, make sure the oil level in the reservoir is correct. The level should be between 2" – 2 1/2" below the top of the oil fill tube. Use fully synthetic oil: Mobil 1 15W-50. Lift the mower so that the rear wheels are off the ground. Be careful to support the mower so that it will not fall or tip while the system is bled of air. With the bypass valves open and the engine running, slowly move the control levers back and forth five or six times. Now close the bypass valves and with the engine running, slowly move the control levers back and forth five or six times. It may be necessary to repeat the above steps until all the air is purged and the rear wheels are turning at normal speed. After purging is complete, adjust the oil level in the reservoir if necessary.

Battery Service

The battery is 12 volts and is a maintenance free battery. Charge the battery only if it will not start the mower properly. Remove the battery from the mower before charging. Follow the instructions of the battery charger for proper and safe charging of the battery.

Cleaning the Mower

The underside of the mower deck should be checked and cleaned twice daily, and more often if the grass being mowed is lush or wet. The entire mower should be cleaned daily at the end of the work day.

Cleaning should be done with a leaf blower or low-pressure compressed air. Wash with water only when necessary and do not use a pressure washer or nozzle as the water can enter electrical connections causing an electrical short, rust and corrosion. When washing with water, do so when the unit has cooled down. Washing a hot machine can cause various unseen system damage. If water is used for cleaning, immediately dry it with a leaf blower or low-pressure compressed air. Once the wash is complete, always lubricate and grease all applicable areas.

* * This Page Intentionally Left Blank * *

MAINTENANCE ITEM	ENGINE ITEMS	SEE NOTE BELOW	FIRST 8 HOURS	DAILY	EVERY 25 HOURS	EVERY 100 HOURS	EVERY 200 HOURS	EVERY 300 HOURS	ANNUALLY
Inspect for cracks in frame, cutter deck or other steel parts		*1	X						X
Inspect all belts for wear, adjustment and alignment			X		X				X
Check all bolts and nuts for tightness (tighten as necessary)			X	X					X
Lubricate hand control lever pivot shafts with waterproof grease			X						X
Check hydraulic oil reservoir level and fill as needed - Use SYNTHETIC oil - Mobil1 15W-50			X			X			
Grease caster wheel bearings			X	X					X
Check tire pressure; Rear tires 18-22 psi-Front tires 30-40 psi. Some Front Casters are			X	X					X
Check and clean engine cooling fins	Engine	*2	X		X				X
Clean hydro cooler debris screen				X					X
Clean hydro cooler				X	X				X
Lubricate Operator Presence Control pivots and control rod with waterproof grease			X		X				X
Replace fuel filter	Engine	*2	X			X			
Lubricate choke control cable with WD-40			X			X			X
Check engine oil and add as needed	Engine	*2		X					X
Check for fuel or oil leakage - correct as needed	Engine	*2		X					X
Check and clean air intake screen	Engine	*2		X					X
Clean engine blower screen and fins with compressed air	Engine	*2		X					X
Clean mower with compressed air-do NOT use a pressure washer				X					X
Check for loose hardware (e-clips, snap rings, nuts, etc.)				X					X
Check blades for wear and sharpness (sharpen and balance or replace as necessary)				X					X
Check and adjust tire pressures to no more than maximum pressure listed on tire for maintaining good traction and comfort				X					X
Clean out debris under blade belt cover				X					X
Scrape clean underside of cutter deck				X					X
Check blade mounting bolts for proper tightness				X					X
Check blade spindle mounting bolts for proper tightness				X					X
Clean air cleaner foam element	Engine	*2		X					X
Inspect tires, replace as needed					X				X
Clean air cleaner paper element	Engine	*2		X					X
Clean and re-gap spark plug (replace as necessary)	Engine	*2				X			X
Change engine oil	Engine	*2	X			X			X
Change engine oil filter	Engine	*2					X		X
Replace air cleaner paper element	Engine	*2					X		X
Replace hydraulic oil filter with Original Wright Filter									X
Completely inspect for excessive wear in all parts of mower, including control system (replace worn parts)							X		X
Inspect and replace (if necessary) worn main cutter deck idler pulleys or pulley bearings (if applicable)							X		X
Replace (if necessary) excessively worn caster wheels and roller bearings							X		X
Remove battery and clean battery, battery box and battery cable ends							X		X
Clean combustion chamber	Engine	*2						X	
Check and adjust valve clearance	Engine	*2						X	
Clean and lap valve seating surface	Engine	*2						X	
NOTES:									
*1 - Contact an authorized Dealer immediately if any cracks are found									
*2 - Refer to Engine Manufacturers Owners Manual									
The service intervals indicated are to be used as a guide. Service should be performed more frequently as necessary by operating conditions									

WRIGHT MANUFACTURING, INC. POWER EQUIPMENT LIMITED WARRANTY

THIS WARRANTY SUPERSEDES ALL PREVIOUS ON UNITS WITH A RETAIL SALES DATE ON OR AFTER 04/01/05

Wright Manufacturing, Inc. (hereinafter: WMI) warrants to the original owner that the new WMI mower accompanying this document will be free from manufacturing defects in materials or workmanship subject to the following limitations and exclusions. Any part of the WMI commercial mower manufactured by WMI and found, in the reasonable judgment of WMI, to be defective in materials or workmanship, will be repaired or replaced by an Authorized WMI Service Dealer without charge for parts and (except as excluded below) labor. This Warranty is limited to the original Owner and the mower this document was provided with and is not transferable. Dealer demo units with less than fifty hours when first retailed shall also be covered by this limited warranty. Proofs of Purchase, Authorized Dealer performed Pre-Deliver Service and the First Eight Hour Service will be required by the Authorized WMI Service Dealer to substantiate any warranty claims. All WMI warranty work must be performed by an Authorized WMI Service Dealer and item must be delivered to the dealer prior to the expiration of the warranty period. This Warranty is limited to the following specified periods from the date of the original retail purchase for defects in materials or workmanship and will commence upon the date of original retail purchase. This warranty shall apply only if the warranty registration form has been completed and returned to Wright Manufacturing, Inc. within 30 days from the date of original retail purchase. This warranty includes only the cost of parts and labor (when applicable). This warranty applies only to the replacement of defective or otherwise warrantable WMI OEM parts being replaced with WMI OEM parts.

- All parts and components (except as noted below) – 2 years
- Belts – 90 days
- Battery – 90 days
- Engine – warranty covered by engine manufacturer and handled through the respective Authorized engine Dealers

Exclusions:

Any damage or deterioration due to normal use, wear and tear or exposure
All filters, engine oil, hydraulic oil, tires and tubes
Bent, fractured or broken parts occurring through impact or hard use
Clutch: linings, anti-rotation failure or other failure due to improper replacement installation
Cost of regular maintenance service, parts or adjustments
Worn bearings (other than spindle bearings; see above)
Worn bushings, cotters, clips, pins and retainers
Grease fittings/zerks
Paint, paint fading, cosmetic imperfections and steel surface imperfections
Fabric, cushion and rubber grip wear or damage
Cutting blades, light bulbs, fuses
Damage due to loose pulleys on shafts
Damage due to loose wheel hubs on tapered hydraulic motor shafts
Fire Damage
Abrasion or corrosion wear or damage

Repair Parts Replaced During Original Warranty

All Repair parts (excluding wear or otherwise excluded items) installed during the warranty period are warranted until the end of the respective original period according to the categories above except in the case that the respective original warranty period expires in less than ninety (90) days after the installation of the part(s). If this happens then the parts are warranted for a total of ninety (90) days from the time of their installation.

Rental Use

The above warranty periods are limited to maximum of ninety (90) days for mowers that are used for rental purposes.

The WMI mower, including any defective part, must be returned to an Authorized WMI Service Dealer within the warranty period. The expense of lost production time and delivering the mower to the Authorized WMI Service Dealer for warranty work and the expense of returning it to the Owner after repair will be paid for by the Owner. WMI's responsibility is limited to making the required repairs and no claim of breach of warranty shall be cause for cancellation or rescission of the contract of sale of any WMI mower. This Warranty does not apply to any mower that was delivered to an Owner prior to the Pre-Delivery Service as specified in the Owner's Manual. This Warranty does not apply to any mower that was shipped in a crate to the Owner or delivered to the Owner by non-employees of an Authorized Dealer. For the Owner's protection and a valid Warranty, please note: WMI does not permit Authorized Dealers to make non-face-to-face deliveries of the mower and any who are found doing so are subject to immediate cancellation as Authorized Dealers. This Warranty does not cover any mower that has been subject to misuse, neglect, negligence, burning in any fire, an accident, or that has been operated or maintained in any way contrary to the operating and maintenance instructions as specified in the Owner's Manual. The Warranty does not apply to any damage to the mower that is the result of improper maintenance, or to any mower or parts that have not been assembled or installed as specified in the Owner's Manual. The Warranty does not cover any mower that has been altered or modified changing performance or durability. In addition, the Warranty does not extend to repairs made necessary by normal wear, or by the use of parts or accessories which, in the reasonable judgment of WMI, are either incompatible with the WMI mower or adversely affect its operation, performance or durability.

WMI reserves the right to change or improve the design of any mower without assuming any obligation to modify any mower previously manufactured.

All other implied warranties are limited in duration to the two (2) year warranty period or ninety (90) days for mowers used for rental purposes. Accordingly, any such implied warranties including merchantability, fitness for a particular purpose, or otherwise, are disclaimed in their entirety after the expiration for the appropriate two (2) year or ninety (90) day warranty period. WMI's obligation under this Warranty is strictly limited to the repair or replacement of defective parts and WMI does not assume, or authorize anyone to assume for them, any other obligation. Some states do not allow limitations on how long an implied warranty lasts, so the above limitation may not apply.

WMI assumes no responsibility for incidental, consequential or other damages including, but not limited to, expense for gasoline, expense of delivering the mower to an Authorized WMI Service Dealer and expense of returning it to the Owner, damage by fire, mechanic's travel time, telephone charges, rental of a like product during the time warranty repairs are being performed, travel, loss or damage to personal property, loss of revenue, loss of use of the power equipment, loss of time or inconvenience. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply.

This Warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

This Warranty applies to all WMI mowers sold in the United States of America and Canada.

For the location of the Authorized WMI Service Dealer nearest you or other information, such as, Parts Lists and Owner's Manuals visit our website at: www.wrightmfg.com

Wright Manufacturing, Inc.
4600-X Wedgewood Blvd.
Frederick, MD 21703



4600X Wedgewood Blvd
Frederick, MD 21703
www.wrightmfg.com